



FASCIA INCLUDES 3 1/2\"/>

- ① STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE THICKER THAN .060\"/>
- ② WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050\"/>

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.

**PERMA-TITE SYSTEM 200 FASCIA DIMENSIONS**

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-80S	8"	6"	3 NAILERS
<input type="checkbox"/> FA-95S	9 1/2"	7 1/2"	4 NAILERS
<input type="checkbox"/> FA-110S	11"	9"	5 NAILERS
<input type="checkbox"/> FA-125S	12 1/2"	10 1/2"	6 NAILERS

ANSI/SPRI/FM 4435/ ES-1  
DESIGN PRESSURE

FA-80 IN 24 GA. OR .040" - 126 psf  
FA-80 IN .050 OR .063" - 196 psf  
FA-95 TO FA-125 IN .050 OR .063" - 97 psf

**AUTHORIZED SIGNATURE:**

APPROVED BY: \_\_\_\_\_

DATE: \_\_\_\_\_

**MATERIAL:**

\_\_\_ 24 GA. GALV. STEEL                      \_\_\_ .050" ALUMINUM  
\_\_\_ .040" ALUMINUM                      \_\_\_ .063" ALUMINUM  
\_\_\_ OTHER \_\_\_\_\_

COLOR: \_\_\_\_\_ FINISH: \_\_\_\_\_

**QUANTITIES:**

\_\_\_\_\_ LINEAL FEET 12'-0" LENGTHS  
\_\_\_\_\_ OUTSIDE MITER(S) @ 90°  
\_\_\_\_\_ INSIDE MITER(S) @ 90°                      SPECIFY ACCESSORY TYPE:  
\_\_\_\_\_ RIGHT ENDCAP(S)                                       WELDED ②  
\_\_\_\_\_ LEFT ENDCAP(S)                                       STANDARD  
\_\_\_\_\_ RIGHT ENDWALL FLASHING(S)  
\_\_\_\_\_ LEFT ENDWALL FLASHING(S)  
\_\_\_\_\_ OVERFLOW SCUPPER(S) STYLE \_\_\_A\_\_\_B  
\_\_\_\_\_ SPILLOUT SCUPPER(S) STYLE \_\_\_A\_\_\_B  
\_\_\_\_\_ DOWNSPOUT SCUPPER(S) STYLE \_\_\_A\_\_\_B  
   ( \_\_\_X\_\_\_ ) SIZE                      A: TAPERED 1 1/2" DROP  
      B: FLAT  
FOR NON-90 MITERS SEE PRINT APPROVAL #11010-1103

PROJECT: \_\_\_\_\_

ARCHITECT: \_\_\_\_\_

ROOFING CONTRACTOR: \_\_\_\_\_

REPRESENTATIVE/DISTRIBUTOR: \_\_\_\_\_