



FASCIA INCLUDES 3 1/2" WIDE SPLICE PLATE AT JOINTS.

- ① STANDARD FASCIA WILL NOT FUNCTION WITH ROOF FLASHING THICKER THAN 3/16".
- ② OIL CANNING CAN OCCUR ON LARGER FACE HEIGHTS. RECOMMEND .050" OR .063" FOR FACE HEIGHTS ABOVE 8 1/4"
- ③ WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.

PERMA-TITE SYSTEM 300 FASCIA DIMENSIONS

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-350	5 1/4"	2 7/8"	1 NAILER
<input type="checkbox"/> FA-365	6 3/4"	4 3/8"	2 NAILERS
<input type="checkbox"/> FA-380	8 1/4"	5 7/8"	3 NAILERS
<input type="checkbox"/> FA-395	9 3/4"	7 3/8"	4 NAILERS
<input type="checkbox"/> FA-3110	11 1/4"	8 7/8"	5 NAILERS
<input type="checkbox"/> FA-3125	12 3/4"	10 3/8"	6 NAILERS

ANSI/SPRI/FM 4435/ ES-1 DESIGN PRESSURE
 FA-50 TO FA-80 IN 24 GA. OR .040" - 196 psf
 FA-50 TO FA-80 IN .050 OR .063" - 216 psf
 FA-95 TO FA-125 IN .050 OR .063" - 116 psf

AUTHORIZED SIGNATURE:

APPROVED BY: _____

DATE: _____

MATERIAL:

___ 24 GA. GALV. STEEL ② ___ .050" ALUMINUM
 ___ .040" ALUMINUM ② ___ .063" ALUMINUM
 ___ OTHER _____

COLOR: _____ FINISH: _____

QUANTITIES:

___ LINEAL FEET 12'-0" LENGTHS
 ___ OUTSIDE MITER(S) @ 90°
 ___ INSIDE MITER(S) @ 90° SPECIFY ACCESSORY TYPE:
 ___ RIGHT ENDCAP(S) WELDED ③
 ___ LEFT ENDCAP(S) STANDARD
 ___ RIGHT ENDWALL FLASHING(S)
 ___ LEFT ENDWALL FLASHING(S)
 ___ OVERFLOW SCUPPER(S) STYLE ___A___B
 ___ SPILLOUT SCUPPER(S) STYLE ___A___B
 ___ DOWNSPOUT SCUPPER(S) STYLE ___A___B
 (___X___) SIZE A: TAPERED 1 1/2" DROP
 B: FLAT
 FOR NON-90 MITERS SEE PRINT APPROVAL #11010-1103

PROJECT: _____
 ARCHITECT: _____
 ROOFING CONTRACTOR: _____
 REPRESENTATIVE/DISTRIBUTOR: _____