




TPO ONE DRIP EDGE


WITH FACTORY APPLIED TPO FLASHING

WITH CONTINUOUS CLEAT



- 3"
- 4"
- 6"
- OTHER _____

MIN. 1 1/4"
MAX. 8"



NOTES:

- NO LAP NOTCHES PROVIDED.
- NO SPLICE PLATES PROVIDED.
- ALL FASTENERS PROVIDED.

Fabrication will proceed only after receipt of signed print approval.

Print Approval:

Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Metal-Era's printed instructions.

Approved by: _____

Date: _____

MATERIAL:

____ 24 Ga. Galv. Steel Carlisle / Versico TPO Coated
With Reinforced Flashing

____ 24 Ga. Galv. Steel GAF TPO Coated
With Non-Reinforced Flashing

COLOR:

White

QUANTITIES:

_____ Lineal Feet (12'-0" Lengths)

_____ Outside Miters @ 90° (TPO Flashing Not Included)

_____ Inside Miters @ 90° (TPO Flashing Not Included)

FOR NON-90° MITERS SEE PRINT APPROVAL #11010-1103

PROJECT:

ARCHITECT:

ROOFING CONTRACTOR:

REPRESENTATIVE/DISTRIBUTOR:

Corporate Offices, Manufacturing
1600 Airport Road; Waukesha, WI 53188
Phone: 800-558-2162
Fax: 800-373-9156
www.metalera.com



DATE: 09/25/18

DRN BY: JJC

CKD BY: SAK

SHT.# ____ OF ____

DWG# 11010-20557 |