REFERENCE DETAIL:

## TECHNI-FLO RV SLOPED ROOF MEETS VERTICAL WALL

.050" EXPANDE METAL SUPPORT SCREE INTERMITTENT SPACER 12" O.C. CONTINUOUS 20 GA. GALV. "Z" BRACKET 8" WIDE COVER PLATE	1 12	THE RIDGE OPENING MAY BE PROVIDED BY ONE OF TWO METHODS:  1. THE ACTUAL KNOWN  RIDGE OPENING OR NFA  OR  2. FIELD OR PLAN CONDITION MEASUREMENTS:
DEFLECTOR (12'-0" LENGTHS TYP. BOTH SIDES) (ONLY REQUIRED IF PITCH IS LESS THAN 4 / 12)  SHINGLED ROOF SHOWN IF STANDING SEAM CONDITION, PLEASE SUPPLY HEIGHT OF STANDING SEAM  ALL FASTENERS AND SEALANT BY OTHERS	ACTUAL WALL SIZE MIN. 3"  22 GA. GALV. CONTINUOUS CLEAT  (ANYTHING LESS THAN A 4 / 12 PITCH REQUIRES DEFLECTORS) ROOF PITCH	ACTUAL LINEAL FOOTAGE OF RIDGE  VENTILATION TYPE:  VENTED NAILBASE  AIR SPACE DIMENSION OF VENTED NAILBASE  OR  ATTIC  ATTIC  RIDGE BEAM WIDTH IF APPLICABLE
Print Approval: Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Atlas Roofing's printed instructions.  Approved by:  Date:	COVER MATERIAL:  24 GA. GALV. STEEL .040" ALUMINUM .050" ALUMINUM .063" ALUMINUM OTHER	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
PROJECT:		Phone: 855-542-0918 Fax: 800-770-3934
ARCHITECT:		Engineered Roof Ventilation atlasroofing.com
CONTRACTOR:		DATE: 08/29/17 SHT.# OF
REPRESENTATIVE:		CKD BY: SAK DWG# 38024-14985 <b>F</b>