


**FASCIA INCLUDES 3 1/2" WIDE SPLICE PLATE AT JOINTS.**

- ① STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE THICKER THAN .060".
- ② OIL CANNING CAN OCCUR ON LARGER FACE HEIGHTS. RECOMMEND .050" OR .063" FOR FACE HEIGHTS ABOVE 8 1/4"
- ③ WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

**NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.**

### PERMA-TITE SYSTEM 200 FASCIA DIMENSIONS

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-50	5 1/4"	2 7/8"	1 NAILER
<input type="checkbox"/> FA-65	6 3/4"	4 3/8"	2 NAILERS
<input type="checkbox"/> FA-80	8 1/4"	5 7/8"	3 NAILERS
<input type="checkbox"/> FA-95	9 3/4"	7 3/8"	4 NAILERS
<input type="checkbox"/> FA-110	11 1/4"	8 7/8"	5 NAILERS
<input type="checkbox"/> FA-125	12 3/4"	10 3/8"	6 NAILERS

**ANSI/SPRI/FM 4435/ ES-1  
DESIGN PRESSURE**

 FA-50 TO FA-80 IN 24 GA. OR .040" - 196 psf  
 FA-50 TO FA-80 IN .050 OR .063" - 216 psf  
 FA-95 TO FA-125 IN .050 OR .063" - 116 psf

**AUTHORIZED SIGNATURE:**
**APPROVED BY:** \_\_\_\_\_

**DATE:** \_\_\_\_\_

**MATERIAL:**

 \_\_\_\_ 24 GA. GALV. STEEL (2)      \_\_\_\_ .050" ALUMINUM  
 \_\_\_\_ .040" ALUMINUM (2)      \_\_\_\_ .063" ALUMINUM  
 \_\_\_\_ OTHER \_\_\_\_\_

COLOR: \_\_\_\_\_ FINISH: \_\_\_\_\_

**QUANTITIES:**

 \_\_\_\_ LINEAL FEET 12'-0" LENGTHS  
 \_\_\_\_ OUTSIDE MITER(S) @ 90°  
 \_\_\_\_ INSIDE MITER(S) @ 90°      SPECIFY ACCESSORY TYPE:  
 \_\_\_\_ RIGHT ENDCAP(S)       WELDED (3)  
 \_\_\_\_ LEFT ENDCAP(S)       STANDARD  
 \_\_\_\_ RIGHT ENDWALL FLASHING(S)  
 \_\_\_\_ LEFT ENDWALL FLASHING(S)  
 \_\_\_\_ OVERFLOW SCUPPER(S) STYLE \_\_\_\_A\_\_\_\_B  
 \_\_\_\_ SPILLOUT SCUPPER(S) STYLE \_\_\_\_A\_\_\_\_B  
 \_\_\_\_ DOWNSPOUT SCUPPER(S) STYLE \_\_\_\_A\_\_\_\_B  
 (\_\_\_\_X\_\_\_\_) SIZE      A: TAPERED 1 1/2" DROP  
    B: FLAT  
**FOR NON-90 MITERS SEE PRINT APPROVAL #16010-2320**

<b>PROJECT:</b>
<b>ARCHITECT:</b>
<b>ROOFING CONTRACTOR:</b>
<b>REPRESENTATIVE/DISTRIBUTOR:</b>

 51 LEXINGTON STREET; LEWISTON, ME 04240  
 CUSTOMER SERVICE: 800-223-8317 USA  
 800-445-1500 CANADA

 TECHNICAL SERVICE: 800-445-1500 USA & CANADA  
 FAX: 207-784-0125  
 OTHER AREAS CALL: 207-784-0123

 DATE: 09/27/16  
 DRN BY: JJC  
 CKD BY: SAK

 SHT.# \_\_\_\_ OF \_\_\_\_  
 DWG# 16010-21542      **E**