





1) STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE THICKER THAN .060".					MATERIAL:			
② OIL CANNING CAN OCCUR ON LARGER FACE HEIGHTS. RECOMMEND .050" OR .063" FOR					24 GA. GALV. STEEL (2)050" ALUMINUM			
FACE HEIGHT		UDE A A41511A411A	A OF MATERIAL THEORY	OF 050ll	040" ALUMINUM (2)		.063" ALUMINUM	
③ WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"					OTHER		.003 /LOMINOM	
NOTE: UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.						— FINICII		
					COLOR:	FINISH:		
FIBERTITE 200 FASCIA DIMENSIONS					QUANTITIES:			
PRODUCT	H		X	NAILER			TI I C	
ID. NO.	DIM		DIM	COVERAGE	LINEAL FEET 12'-0" LENGTHS			
☐ FA-65	5 1/4" 6 3/4"		2 7/8" 4 3/8"	1 NAILER 2 NAILERS	OUTSIDE MITER(S) @ 90°		CDE CIEV	
☐ FA-80	8 1/		5 7/8"	3 NAILERS	INSIDE MITER(S) @	90° و	SPECIFY ACCESSORY TYPE:	
☐ FA-95	9 3,		7 3/8"	4 NAILERS	RIGHT ENDCAP(S))	_	
☐ FA-110	11 1/4"		8 7/8"	5 NAILERS			□ WELDED ③□ STANDARD	
☐ FA-125	12 :	3/4"	10 3/8"	6 NAILERS	RIGHT ENDWALL	EL ASHING(S)		
FA-50 TO FA-80 IN 24 GA. OR .040" - 196 p			.040" - 196 psf	· · · · · · · · · · · · · · · · · · ·				
ANSI/SPRI/FM 4435/ ES-1 DESIGN PRESSURE		FA-50 TO FA-80 IN .050 OR .063" - 216 psf			LEFT ENDWALL FLASHING(S)			
		FA-95 TO FA-125 IN .050 OR .063" - 116 psf			OVERFLOW SCUPPER(S) STYLEAB			
AUTHORIZED SIGNATURE:					SPILLOUT SCUPPER(S) STYLEAB			
AUTHONIZED SIGNATURE.					DOWNSPOUT SCUPPER(S) STYLEAB			
APPROVED BY:					(X) SI:	/ -	APERED 1 1/2" DROP	
DATE:					B: FLAT FOR NON-90 MITERS SEE PRINT APPROVAL #23010-2417			
PROJECT:								
ARCHITECT:								
ROOFING COI	NTRACTOR:							
REPRESENTAT	IVE/DISTRI	BUTOR:						
CUCTOMER CERVICE					DATE:	09/23/16	SHT.# OF	
CUSTOMER SERVICE 800-355-6416					DRN B			
230 233 0 110					CKD B	Y-SAK DW	VG# 23010-21532 E	

CKD BY: SAK