REFERENCE DETAIL:

HI-PERF RIDGE VENT
SLOPE TO SLOPE, STANDING SEAM VERSION

ENDCAPS

THE RIDGE OPENING MAY BE PROVIDED BY ONE OF TWO METHODS:

1. THE ACTUAL KNOWN

ALL FASTENERS ANI SEALANT BY OTHER		THE RIDGE OPENING MAY BE PROVIDED BY ONE OF TWO METHODS: 1. THE ACTUAL KNOWN
INTERMITTENT SPACER ¬ 12" O.C. .050 EXPANDED ¬ METAL SUPPORT SCREEN \ /	RIDGE VENT COVER STYLE A STYLE B (12-0" LENGTHS)	RIDGE OR NFA OR
STANDING SEAM HEIGHT HEM	COVER PLATE AT EACH JOINT	2. FIELD OR PLAN CONDITION MEASUREMENTS: ACTUAL LINEAL FOOTAGE OF RIDGE ACTUAL LINEAL FOOTAGE OF EAVE
RIDGE OPENING DIMENSION 3½" WIDE DEFLECTOR BAFFLE AT DEFLECTOR	CONTINUOUS 20 GA. GALV. Z BRACKET	VENTILATION TYPE: VENTED NAILBASE AIR SPACE DIMENSION OF VENTED NAILBASE OR
JOINTS DEFLECTOR (12'-0" LENGTHS TYP. BOTH SIDES) (ONLY REQUIRED IF PITCH IS LESS THAN 4 / 12)	12 (ANYTHING LESS THAN A 4 / 12 PITCH REQUIRES DEFLECTORS) ROOF PITCH	ATTIC ATTIC FLOOR SQUARE FOOTAGE RIDGE BEAM WIDTH IF APPLICABLE
Fabrication will proceed only after receipt of signed print approval. Print Approval: Architect and/or contractor shall verify all dimensions, sizes	COVER MATERIAL:	QUANTITIES: JMINUM LINEAL FEET (12'-0" LENGTHS)
and quantities. All products to be installed in strict accordance with Metal-Era's printed instructions. Approved by:	24 GA. GALV. STEEL .040" ALU. .063" ALU. .063" ALU. .063" ALU. .0640" ALU.	
Date:	COLOR: FINISH:	
PROJECT:		Phone: 800-558-2162 Fax: 800-770-3934
ARCHITECT:		Airflow Solutions www.metalera.com
CONTRACTOR:		DATE: 07/27/17 SHT.# OF
REPRESENTATIVE:		CKD BY: SAK DWG# 31024-14088 G