



SEAL-TITE WR GUTTER

OFFSET

*NOTES

- Bottom sizes are provided in 1/2" increments
- Maximum downspout dimension not to exceed "B" minus 1- 9/16"
- Roof flange is optional. If flange size is not provided, the gutter will not include a roof flange. If flange angle is not provided, the gutter will have a 90-degree flange.
- Pop rivets provided
- Unless otherwise noted, fabrication of miters and accessories are provided with a non- penetrating quicklock joint, then factory sealed watertight
- Welded accessories require minimum material thickness of .050 aluminum.
- For non-90 miters, see separate print approval
- Product should be installed per provided installation instructions
- ANSI/SPRI GT-1 Test Pressure up to 223 psf (Horizontal) and 136 psf (Vertical)

APPROVALS*



ANSI/SPRI/GT-1
Test Pressures listed in notes

PROJECT INFO

Project Name: _____

Architect: _____

Roofing Contractor: _____


Project Type:

By selecting this box you have verified and confirmed that dimensions, sizes, and quantities are correct. All products will be installed in strict accordance with printed instructions.

Date: _____

Metal-Era LLC
1600 Airport Rd.
Waukesha, WI 53188
Phone: 800-558-2162
www.metalera.com

SHT# _____ of _____
DATE: **11/16/23**
DRN BY: **PL**
CKD BY: **MM**
DWG #: **11012-38910**
REV: **B**



DIMENSIONS

| SELECT SIZE | A (FACE) | B (BOTTOM) | C (BACK) | FLANGE (OPTIONAL) |
|--------------------------|----------|------------|----------|--|
| <input type="checkbox"/> | 5 1/4" | 5 1/4" | 6 1/4" | D (FLANGE SIZE) (MAX 8"/MAX TESTED 4") NOTE: IF SIZE IS NOT PROVIDED, GUTTER WILL NOT INCLUDE A ROOF FLANGE |
| <input type="checkbox"/> | 5 3/4" | 5 3/4" | 6 3/4" | |
| <input type="checkbox"/> | 6 1/4" | 6 1/4" | 7 1/4" | |
| <input type="checkbox"/> | 6 3/4" | 6 3/4" | 7 3/4" | |
| <input type="checkbox"/> | 7 1/4" | 7 1/4" | 8 1/4" | |
| <input type="checkbox"/> | 7 3/4" | 7 3/4" | 8 3/4" | E (FLANGE ANGLE) NOTE: IF ANGLE IS NOT PROVIDED, FLANGE WILL BE 90° |

MATERIAL

- 24 Ga. Galv. Steel
 - 22 Ga. Galv. Steel
 - .040" Aluminum
 - .050" Aluminum
 - .063" Aluminum
 - OTHER: _____
- Color: _____
Finish: _____
- Substrate:
If substrate is not given, wood fasteners will be provided.
- Wood
 - Masonry
 - Metal



QUANTITIES

- _____ Lineal Feet (12'-0" Lengths)
- _____ Outside Miter (90°)
- _____ Inside Miter (90°)
- _____ Right Endcaps
- _____ Left Endcaps
- _____ Expansion Joints (If Required)


Accessory Type*: Quicklock (Default) Welded (Surcharge)

SEAL-TITE WR GUTTER


OFFSET STANDARD ACCESSORIES



OUTSIDE MITER




INSIDE MITER



END CAP

LEFT HAND SHOWN



EXPANSION JOINT
(IF REQUIRED)

Standard gutter miter leg lengths are 24" Nominal
Standard gutter miter angle is 90°
For special miter requirements, attach sketches or consult manufacturer for assistance.

SHT# ____ of ____

DATE: **11/16/23**

DRN BY: **PL**

CKD BY: **MM**

DWG #: **11012-38910**

REV: **B**

Metal-Era LLC
1600 Airport Rd.
Waukesha, WI 53188
Fax: 800-558-2162
www.metalera.com