



FIBERTITE WR GUTTER
CHAMFER

FM DESIGN

*NOTES

- Bottom sizes are provided in 1/2" increments
- Maximum downspout dimension not to exceed "B" minus 2-1/16"
- Roof flange is optional. If flange size is not provided, the gutter will not include a roof flange. If flange angle not provided, the gutter will have a 90-degree flange.
- Pop rivets provided
- Unless otherwise noted, fabrication of miters and accessories are provided with a non- penetrating quicklock joint, then factory sealed watertight
- Welded accessories require minimum material thickness of .050 aluminum.
- For non-90 miters, see separate print approval
- Product should be installed per provided installation instructions
- ANSI/SPRI/GT-1 test pressures up to 596 psf (Horizontal), 224 psf (Vertical), 160 plf (Downward)

APPROVALS*



ANSI/SPRI/GT-1
Test Pressures listed in notes

PROJECT INFO

Project Name: _____

Architect: _____

Roofing Contractor: _____

Project Type:

☐ By selecting this box you have verified and confirmed that dimensions, sizes, and quantities are correct. All products will be installed in strict accordance with printed instructions.

Date: _____

SHT# _____ of _____


DATE: **06/03/25**

DRN BY: **MLM**

CKD BY: **MM**

DWG #: **23012-44779**

REV: **A**



DIMENSIONS

SELECT SIZE	A (FACE)	B (BOTTOM)	C (BACK)	FLANGE (OPTIONAL)
☐	5 1/4"	5 1/4"	6 1/4"	D (FLANGE) PLEASE SELECT ONE: WITH FLANGE ☐ WITHOUT FLANGE ☐ NOTE: IF NEITHER BOX IS CHECKED, THE GUTTER WILL BE PROVIDED WITHOUT A ROOF FLANGE
☐	5 3/4"	5 3/4"	6 3/4"	
☐	6 1/4"	6 1/4"	7 1/4"	
☐	6 3/4"	6 3/4"	7 3/4"	
☐	7 1/4"	7 1/4"	8 1/4"	
☐	7 3/4"	7 3/4"	8 3/4"	
				E (FLANGE ANGLE) NOTE: IF ANGLE IS NOT PROVIDED, FLANGE WILL BE 90° _____

MATERIAL

☐ 24 Ga. Galv. Steel

☐ 22 Ga. Galv. Steel

☐ .040" Aluminum

☐ .050" Aluminum

☐ .063" Aluminum

☐ OTHER: _____

Color: _____

Finish: _____

Substrate: _____

If substrate is not given, wood fasteners will be provided.

☐ Wood

☐ Masonry

☐ Metal

QUANTITIES

Accessory Type*: ☐ Quicklock (Default) ☐ Welded (Surcharge)

_____ Lineal Feet (12'-0" Lengths)

_____ Outside Miter (90°)

_____ Inside Miter (90°)

_____ Right Endcaps



_____ Left Endcaps

_____ Expansion Joints (If Required)




FIBERTITE WR GUTTER CHAMFER STANDARD ACCESSORIES


FM DESIGN




INSIDE MITER



OUTSIDE MITER



END CAP
LEFT HAND SHOWN



EXPANSION JOINT
(IF REQUIRED)

Standard gutter miter leg lengths are 24" Nominal
Standard gutter miter angle is 90°
For special miter requirements, attach sketches or consult manufacturer for assistance.

FiberTite
Customer Service
1-800-355-6416

SHT# ____ of ____

DATE: **06/03/25**

DRN BY: **MLM**

CKD BY: **MM**

DWG #: **23012-44779**

REV: **A**