REFERENCE DETAIL:		HI-PERF RIDGE VENT
		SLOPE TO SLOPE, STANDING SEAM VERSION
		FOR HIGH SNOW LOAD CONDITIONS
ALL FASTENERS AN		THE RIDGE OPENING MAY BE PROVIDED BY ONE OF TWO METHODS:  U.S. PATENT PENDING
SEALANT BY OTHER		1. THE ACTUAL KNOWN
INTERMITTENT SPACER – 12" O.C.	RIDGE VENT COVER STYLE A STYLE B (12-0" LENGTHS)	RIDGE OR OPENING OR
.050 EXPANDED \ METAL SUPPORT SCREEN \	/ 8" WIDE COVER PLATE	OR
STANDING SEAM HEIGHT - 7/16" HEM	AT EACH JOINT	2. FIELD OR PLAN CONDITION MEASUREMENTS:
		ACTUAL LINEAL FOOTAGE OF RIDGE ACTUAL LINEAL FOOTAGE OF EAVE
		VENTILATION TYPE:
RIDGE OPENING		☐ VENTED NAILBASE
DIMENSION  3½" WIDE DEFLECTOR	CONTINUOUS 20 GA. GALV.	AIR SPACE DIMENSION OF VENTED NAILBASE
BAFFLE AT DEFLECTOR JOINTS	Z BRACKET	OR
DEFLECTOR (12'-0" LENGTHS —	12 (ANYTHING LESS	☐ ATTIC
TYP. BOTH SIDES) (ONLY REQUIRED IF PITCH IS	THAN A 4 / 12 PITCH	ATTIC FLOOR SQUARE FOOTAGE
LESS THAN 4 / 12)	ROOF PITCH	RIDGE BEAM WIDTH IF APPLICABLE
Fabrication will proceed only after receipt of signed print approval.  Print Approval:	COVER MATERIAL:	QUANTITIES:
Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance	.050" ALUMINUM	LINEAL FEET (12'-0" LENGTHS)
with Metal-Era's printed instructions.	OTHER	ENDCAP(S) (12" LENGTHS, COVER ONLY)
Approved by:		STYLE A STYLE B
Date:	COLOR: FINISH:	
PROJECT:		Phone: 800-558-2162 Fax: 800-770-3934
ARCHITECT:		Airflow Solutions www.metalera.com
CONTRACTOR:		DATE: 07/27/17   SHT.# OF
REPRESENTATIVE:		CKD BY: SAK DWG# 31024-14087