REFERENCE DETAIL:	l
	l
	l

## TECHNI-FLO RV SLOPE TO SLOPE, SHINGLED, FIELD ROOFED VERSION

7 RRACKET INTERMITTENT SPACERS AND EXPANDED METAL SUPPORT SCREEN ARE ALL EACTORY ASSEMBLED.

	,	37110 271 71110 20 1	WEITHE SOFT ONLY SCREEN ARE ALL FACTORY ASSEMBLED
STYLE A STYLE B  INTERMITTENT SPACER—  6" WIDE—  CONCEALED SPLICE	- PLYWOOD FOR APPLICATION OF ROOFING MATERIALS (BY OTHERS) 050 EXP	PLYWOOD THICKNESS ANDED SUPPORT SCREEN	THE RIDGE OPENING MAY BE PROVIDED BY ONE OF TWO METHODS:  1. THE ACTUAL KNOWN  RIDGE OPENING OR NFA  OR
PLATE AT EACH JOINT  PROVIDED  DRIP EDGE (12-0" LENGTHS)  7/16" HEM	METAL	— EXISTING SHINGLED ROOF	2. FIELD OR PLAN CONDITION MEASUREMENTS:  ACTUAL LINEAL FOOTAGE OF RIDGE  ACTUAL LINEAL FOOTAGE OF EAVE
RIDGE OPENING DIMENSION  3½" WIDE DEFLECTOR BAFFLE AT DEFLECTOR JOINTS	CONTINUOUS GALV. Z BRAC		VENTILATION TYPE:  VENTED NAILBASE  AIR SPACE DIMENSION OF VENTED NAILBASE  OR
DEFLECTOR (12'-0" LENGTHS TYP. BOTH SIDES) (ONLY REQUIRED IF PITCH IS LESS THAN 4 / 12)	(ANYTHIN THAN A 4	IG LESS / 12 PITCH DEFLECTORS) ALL FASTENERS AND SEALANT BY OTHERS	ATTIC ATTIC FLOOR SQUARE FOOTAGE RIDGE BEAM WIDTH IF APPLICABLE
Fabrication will proceed only after receipt of signed print approval.  Print Approval:  Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Atlas Roofing's printed instructions.  Approved by:  Date:	COVER MATERIAL:  24 GA. GALV. STEEL  050" ALUMINUM  OTHER  COLOR:		MINUM ENDCAP INSERT(S) ( COVER ONLY) STYLE A STYLE B
PROJECT:  ARCHITECT:			Phone: 855-542-0918 Fax: 800-770-3934 Engineered Roof Ventilation atlasroofing.com
CONTRACTOR:			DATE: 08/29/17 SHT.# OF
REPRESENTATIVE:			CKD BY: SAK DWG# 38024-23652 C