


REFERENCE DETAIL:


# TECHNI-FLO RV

SLOPE TO SLOPE, STANDING SEAM, FIELD ROOFED VERSION

**ENDCAPS INSERTS**



STYLE A



STYLE B

INTERMITTENT SPACER  
12" O.C.

.050 EXPANDED  
METAL SUPPORT SCREEN

PLYWOOD FOR  
APPLICATION OF  
ROOFING MATERIALS  
(BY OTHERS)

6" WIDE  
CONCEALED SPLICE  
PLATE AT EACH JOINT

PROVIDED  
DRIP EDGE  
(12'-0" LENGTHS)

STANDING  
SEAM  
HEIGHT

7/16" HEM

DEFLECTOR (12'-0" LENGTHS  
TYP. BOTH SIDES)  
(ONLY REQUIRED IF PITCH IS  
LESS THAN 4 / 12)

3 1/2" WIDE DEFLECTOR  
BAFFLE AT DEFLECTOR  
JOINTS

RIDGE OPENING  
DIMENSION

CONTINUOUS 20 GA.  
GALV. Z BRACKET

12

ROOF PITCH  
(ANYTHING LESS  
THAN A 4 / 12 PITCH  
REQUIRES DEFLECTORS)

PLYWOOD  
THICKNESS

ALL FASTENERS AND  
SEALANT BY OTHERS

THE RIDGE OPENING MAY BE PROVIDED  
BY ONE OF TWO METHODS:

1. THE ACTUAL KNOWN

RIDGE  
OPENING

OR

NFA

OR

2. FIELD OR PLAN CONDITION MEASUREMENTS:

ACTUAL LINEAL  
FOOTAGE OF RIDGE

ACTUAL LINEAL  
FOOTAGE OF EAVE

VENTILATION TYPE:

VENTED NAILBASE

\_\_\_\_ AIR SPACE DIMENSION OF VENTED NAILBASE

OR

ATTIC

\_\_\_\_ ATTIC FLOOR SQUARE FOOTAGE

\_\_\_\_ RIDGE BEAM WIDTH IF APPLICABLE

Fabrication will proceed only after receipt of signed print approval.

## Print Approval:

Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Atlas Roofing's printed instructions.

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

### COVER MATERIAL:

24 GA. GALV. STEEL

.040" ALUMINUM

.050" ALUMINUM

.063" ALUMINUM

OTHER \_\_\_\_\_

COLOR: \_\_\_\_\_

FINISH: \_\_\_\_\_

### QUANTITIES:

\_\_\_\_ LINEAL FEET (12'-0" LENGTHS)

\_\_\_\_ ENDCAP INSERT(S) (COVER ONLY)

\_\_\_\_ STYLE A    \_\_\_\_ STYLE B

PROJECT:

ARCHITECT:

CONTRACTOR:

REPRESENTATIVE:



**Techni-Flo**  
Engineered Roof Ventilation

Phone: 855-542-0918

Fax: 800-770-3934

atlasroofing.com

DATE: 08/29/17

SHT.# \_\_\_\_ OF \_\_\_\_

DRN BY: JAB

CKD BY: SAK

DWG# 38024-16284

E