



FASCIA INCLUDES 3 1/2"
WIDE SPLICE PLATE AT JOINTS.

- ① STANDARD FASCIA WILL NOT FUNCTION WITH ROOF FLASHING THICKER THAN $\frac{3}{16}$ ".
- ② WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.

DERBIGUM PERMA-TITE SYSTEM 300 FASCIA DIMENSIONS

| PRODUCT ID. NO. | H DIM | X DIM | NAILER COVERAGE |
|-----------------------------------|---------|---------|-----------------|
| <input type="checkbox"/> FA-395S | 9 3/4" | 7 3/8" | 4 NAILERS |
| <input type="checkbox"/> FA-3110S | 11 1/4" | 8 7/8" | 5 NAILERS |
| <input type="checkbox"/> FA-3125S | 12 3/4" | 10 3/8" | 6 NAILERS |

ANSI/SPRI/FM 4435/ ES-1
DESIGN PRESSURE

FA-395 TO FA-3125 IN .050 OR .063" - 116 psf

AUTHORIZED SIGNATURE:

APPROVED BY: _____

DATE: _____

MATERIAL:

____ 24 GA. GALV. STEEL ____ .050" ALUMINUM
 ____ .040" ALUMINUM ____ .063" ALUMINUM
 ____ OTHER _____

COLOR: FINISH:

QUANTITIES:

_____ LINEAL FEET 12'-0" LENGTHS

_____ OUTSIDE MITER(S) @ 90°

_____ INSIDE MITER(S) @ 90°

_____ RIGHT ENDCAP(S)

_____ LEFT ENDCAP(S)

_____ RIGHT ENDWALL FLASHING(S)

_____ LEFT ENDWALL FLASHING(S)

_____ OVERFLOW SCUPPER(S) STYLE _____ A _____ B

_____ SPILLOUT SCUPPER(S) STYLE _____ A _____ B

_____ DOWNSPOUT SCUPPER(S) STYLE _____ A _____ B

(_____ X _____) SIZE

SPECIFY
ACCESSORY TYPE:

☐ WELDED ②

☐ STANDARD

A: TAPERED 1 1/2" DROP

B: FLAT

FOR NON-90 MITERS SEE PRINT APPROVAL #20010-25649

PROJECT:

ARCHITECT:

ROOFING CONTRACTOR:

REPRESENTATIVE/DISTRIBUTOR:

CUSTOMER SERVICE
1-800-727-9872

DATE: 02/11/17

DRN BY: JJC

CKD BY: SAK

SHT.# OF

DWG# 20310-25665

A