


ONE DRIP EDGE

COLOR PVC COATED WITH FACTORY-APPLIED PVC FLASHING



NOTES

- All cleats provided in 12'-0" lengths
- All covers provided in 8'-0" lengths
- Miters do not have factory-applied PVC Flashing
- No lap notches or splice plates provided
- For non-90 miters, see separate print approval
- Product should be installed per provided installation instructions
- ANSI/SPRI/FM 4435/ES-1 Test Pressure up to 282 psf

APPROVALS



ANSI/SPRI/FM 4435/ES-1
Test Pressures listed in notes

PROJECT INFO

Project Name: _____

Architect: _____

Roofing Contractor: _____

Project Type:

By selecting this box you have verified and confirmed that dimensions, sizes, and quantities are correct. All products will be installed in strict accordance with printed instructions.

Date: _____

Metal-Era LLC
1600 Airport Rd.
Waukesha, WI 53188
Phone: 800-558-2162
www.metalera.com

SHT# 1 of 1

DATE: 09/07/22

DRN BY: JJC

CKD BY: MM

DWG #: 11010-31566

REV: D

DIMENSIONS

Choose Face Height Size (H Dimension)

- 3"
- 4"
- 6"
- OTHER (MIN: 1.25" MAX: 8"): _____

MATERIAL

24 ga. Galv Steel PVC Coated (Sika Sarnaclad) with Factory Applied Flashing

Color:

- Substrate:** Wood
 Masonry
 Metal
- If substrate is not given, wood fasteners will be provided.

QUANTITIES

_____ Lineal Feet (8'-0" Lengths)

_____ Outside Miter (90°)

_____ Inside Miter (90°)