REFERENCE DETAIL:]

HI-PERF RIDGE VENT SLOPED ROOF MEETS VERTICAL WALL

.050" EXPANDE METAL SUPPORT SCREE INTERMITTENT SPACER 12" O.C. CONTINUOUS 20 GA. GALV. "Z" BRACKET		THE RIDGE OPENING MAY BE PROVIDED BY ONE OF TWO METHODS: 1. THE ACTUAL KNOWN RIDGE OPENING OR NFA
8" WIDE COVER PLATE 7/16" HEM DEFLECTOR (12'-0" LENGTHS TYP. BOTH SIDES) (ONLY REQUIRED IF PITCH IS LESS THAN 4 / 12) SHINGLED ROOF SHOWN IF STANDING SEAM CONDITION, PLEASE SUPPLY HEIGHT OF STANDING SEAM ALL FASTENERS AND SEALANT BY OTHERS	COVERAGE ACTUAL WALL SIZE MIN. 3" 22 GA. GALV. CONTINUOUS CLEAT 12 (ANYTHING LESS THAN A 4 / 12 PITCH REQUIRES DEFLECTORS) ROOF PITCH	2. FIELD OR PLAN CONDITION MEASUREMENTS: ACTUAL LINEAL FOOTAGE OF RIDGE VENTILATION TYPE: VENTED NAILBASE AIR SPACE DIMENSION OF VENTED NAILBASE OR ATTIC ATTIC FLOOR SQUARE FOOTAGE RIDGE BEAM WIDTH IF APPLICABLE
Fabrication will proceed only after receipt of signed print approval. Print Approval: Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Metal-Era's printed instructions. Approved by: Date:	COVER MATERIAL: 24 GA. GALV. STEEL .040" ALUMINUM .063" ALUMINUM	` ,
PROJECT: ARCHITECT:		Phone: 800-558-2162 Fax: 800-770-3934 www.metalera.com
CONTRACTOR:		DATE: 07/27/17 SHT.# OF
REPRESENTATIVE:		DRN BY: JAB CKD BY: SAK DWG# 31024-14740 G