REFERENCE DETAIL:	HI-PERF RAKE PANEL		
			WITHOUT VERTICAL "Z" BRACKETS
	"MIN. ON HEATHING PANEL COVER 12'-0" LENGTH	3	SLOTS "O.C. 7/16" 5/8" COVER DETAIL
PANEL IS TO BE INSTALLED PER SPECIFICATIONS AND METAL-ERA'S INSTALLATION INSTRUCTIONS DWG. # 31127-7385 NOTE: ALL FASTENERS BY OTHERS (SEE INSTALLATION INSTRUCTIONS FOR RECOMMENDATIONS) COVER SHIPPED LOOSE			
"H" DIMENSION:		COVER	: :
☐ 6" COVERAGE ☐ 8" COVERAGE	☐ 10" COVERAGE		A. GALVANIZED STEEL 22 GA. GALVANIZED STEEL
☐ 12" COVERAGE ☐ 14" COVERAGE	☐ 16" COVERAGE		ALLIMINUM .050" ALUMINUM
OTHER:		_	ALUMINUM OTHER
rabrication will proceed only after receipt of signed print approval.			
Print Approval: Architect and/or contractor shall verify all dimensions, sizes QUAN		QUANT	IIIIE2:
and quantities. All products to be installed in strict accordance with Metal-Era's printed instructions.		LINEAL FEET (12'-0" LENGTHS)	
Approved by:			PEAK MITERS
			E ADDITIONAL PRINT APPROVAL FOR RAKE CONDITION
PROJECT:			Phone: 800-558-2162
ARCHITECT:			Airflow Solutions Fax: 800-770-3934 www.metalera.com
CONTRACTOR:			DATE: 09/27/22 SHT.# OF

DRN BY: MLM

CKD BY: MM

DWG# 31027-7449

REPRESENTATIVE: