



- ① STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE THICKER THAN .060".
- ② OIL CANNING CAN OCCUR ON LARGER FACE HEIGHTS. RECOMMEND .050" OR .063" FOR FACE HEIGHTS ABOVE 8 1/4"
- ③ WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.

**PERMA-TITE SYSTEM 200 FASCIA DIMENSIONS**

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-50	5 1/4"	2 7/8"	1 NAILER
<input type="checkbox"/> FA-65	6 3/4"	4 3/8"	2 NAILERS
<input type="checkbox"/> FA-80	8 1/4"	5 7/8"	3 NAILERS
<input type="checkbox"/> FA-95	9 3/4"	7 3/8"	4 NAILERS
<input type="checkbox"/> FA-110	11 1/4"	8 7/8"	5 NAILERS
<input type="checkbox"/> FA-125	12 3/4"	10 3/8"	6 NAILERS

ANSI/SPRI/FM 4435/ ES-1 DESIGN PRESSURE  
 FA-50 TO FA-80 IN 24 GA. OR .040" - 196 psf  
 FA-50 TO FA-80 IN .050 OR .063" - 216 psf  
 FA-95 TO FA-125 IN .050 OR .063" - 116 psf

**AUTHORIZED SIGNATURE:**

APPROVED BY: \_\_\_\_\_

DATE: \_\_\_\_\_

**MATERIAL:**

\_\_\_ 24 GA. GALV. STEEL ②      \_\_\_ .050" ALUMINUM  
 \_\_\_ .040" ALUMINUM ②      \_\_\_ .063" ALUMINUM  
 \_\_\_ OTHER \_\_\_\_\_

COLOR: \_\_\_\_\_ FINISH: \_\_\_\_\_

**QUANTITIES:**

\_\_\_\_\_ LINEAL FEET 12'-0" LENGTHS  
 \_\_\_\_\_ OUTSIDE MITER(S) @ 90°  
 \_\_\_\_\_ INSIDE MITER(S) @ 90°      SPECIFY ACCESSORY TYPE:  
 \_\_\_\_\_ RIGHT ENDCAP(S)       WELDED ③  
 \_\_\_\_\_ LEFT ENDCAP(S)       STANDARD  
 \_\_\_\_\_ RIGHT ENDWALL FLASHING(S)  
 \_\_\_\_\_ LEFT ENDWALL FLASHING(S)  
 \_\_\_\_\_ OVERFLOW SCUPPER(S) STYLE \_\_\_A\_\_\_B  
 \_\_\_\_\_ SPILLOUT SCUPPER(S) STYLE \_\_\_A\_\_\_B  
 \_\_\_\_\_ DOWNSPOUT SCUPPER(S) STYLE \_\_\_A\_\_\_B  
 ( \_\_\_X\_\_\_ ) SIZE      A: TAPERED 1 1/2" DROP  
    B: FLAT

FOR NON-90 MITERS SEE PRINT APPROVAL #11010-1103

PROJECT: \_\_\_\_\_

ARCHITECT: \_\_\_\_\_

ROOFING CONTRACTOR: \_\_\_\_\_

REPRESENTATIVE/DISTRIBUTOR: \_\_\_\_\_