



FASCIA INCLUDES 3 1/2" WIDE SPLICE PLATE AT JOINTS.

- ① STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE THICKER THAN .060".
- ② WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.

FIBERTITE 200 FASCIA DIMENSIONS

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-80S	8"	6"	3 NAILERS
<input type="checkbox"/> FA-95S	9 1/2"	7 1/2"	4 NAILERS
<input type="checkbox"/> FA-110S	11"	9"	5 NAILERS
<input type="checkbox"/> FA-125S	12 1/2"	10 1/2"	6 NAILERS

ANSI/SPRI/FM 4435/ ES-1
DESIGN PRESSURE

FA-80 IN 24 GA. OR .040" - 126 psf
 FA-80 IN .050 OR .063" - 196 psf
 FA-95 TO FA-125 IN .050 OR .063" - 97 psf

AUTHORIZED SIGNATURE:

APPROVED BY: _____

DATE: _____

MATERIAL:

___ 24 GA. GALV. STEEL ___ .050" ALUMINUM
 ___ .040" ALUMINUM ___ .063" ALUMINUM
 ___ OTHER _____

COLOR: _____ FINISH: _____

QUANTITIES:

___ LINEAL FEET 12'-0" LENGTHS
 ___ OUTSIDE MITER(S) @ 90°
 ___ INSIDE MITER(S) @ 90°
 ___ RIGHT ENDCAP(S)
 ___ LEFT ENDCAP(S)
 ___ RIGHT ENDWALL FLASHING(S)
 ___ LEFT ENDWALL FLASHING(S)
 ___ OVERFLOW SCUPPER(S) STYLE ___A___B
 ___ SPILLOUT SCUPPER(S) STYLE ___A___B
 ___ DOWNSPOUT SCUPPER(S) STYLE ___A___B
 (___X___) SIZE A: TAPERED 1 1/2" DROP
 B: FLAT

SPECIFY ACCESSORY TYPE:
 WELDED ②
 STANDARD

FOR NON-90 MITERS SEE PRINT APPROVAL #23010-2417

PROJECT: _____

ARCHITECT: _____

ROOFING CONTRACTOR: _____

REPRESENTATIVE/DISTRIBUTOR: _____

CUSTOMER SERVICE 800-355-6416	DATE: 11/02/16	SHT.# ___ OF ___	
	DRN BY: JJC		
	CKD BY: SAK	DWG# 23010-21590	C