



FASCIA INCLUDES 3 1/2" WIDE SPLICE PLATE AT JOINTS.

- ① STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE THICKER THAN .060".
- ② OIL CANNING CAN OCCUR ON LARGER FACE HEIGHTS. RECOMMEND .050" OR .063" FOR FACE HEIGHTS ABOVE 8"
- ③ WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.

VERSITRIM SYSTEM 200 FASCIA DIMENSIONS

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-50	5"	3"	1 NAILER
<input type="checkbox"/> FA-65	6 1/2"	4 1/2"	2 NAILERS
<input type="checkbox"/> FA-80	8"	6"	3 NAILERS
<input type="checkbox"/> FA-95	9 1/2"	7 1/2"	4 NAILERS
<input type="checkbox"/> FA-110	11"	9"	5 NAILERS
<input type="checkbox"/> FA-125	12 1/2"	10 1/2"	6 NAILERS

ANSI/SPRI/FM 4435/ ES-1 DESIGN PRESSURE
 FA-50 TO FA-80 IN 24 GA. OR .040" - 126 psf
 FA-50 TO FA-80 IN .050 OR .063" - 196 psf
 FA-95 TO FA-125 IN .050 OR .063" - 97 psf

AUTHORIZED SIGNATURE:

APPROVED BY: _____

DATE: _____

MATERIAL:

- ___ 24 GA. GALV. STEEL ②
- ___ .040" ALUMINUM ②
- ___ OTHER _____
- ___ .050" ALUMINUM
- ___ .063" ALUMINUM

COLOR: _____ FINISH: _____

QUANTITIES:

- _____ LINEAL FEET 12'-0" LENGTHS
 - _____ OUTSIDE MITER(S) @ 90°
 - _____ INSIDE MITER(S) @ 90°
 - _____ RIGHT ENDCAP(S)
 - _____ LEFT ENDCAP(S)
 - _____ RIGHT ENDWALL FLASHING(S)
 - _____ LEFT ENDWALL FLASHING(S)
 - _____ OVERFLOW SCUPPER(S) STYLE ___A___B
 - _____ SPILLOUT SCUPPER(S) STYLE ___A___B
 - _____ DOWNSPOUT SCUPPER(S) STYLE ___A___B
 - (___X___) SIZE
- SPECIFY ACCESSORY TYPE:
 WELDED ③
 STANDARD
- A: TAPERED 1 1/2" DROP
 B: FLAT

FOR NON-90 MITERS SEE PRINT APPROVAL #18010-2039

PROJECT:

ARCHITECT:

ROOFING CONTRACTOR:

REPRESENTATIVE/DISTRIBUTOR:

CUSTOMER SERVICE
800-558-2162
(METAL-ERA)

DATE: 09/27/16

DRN BY: JJC

CKD BY: SAK

SHT.# ___ OF ___

DWG# 18010-21635

C