


NON 90° ANGLE FOR FASCIA

MEASUREMENT WORKSHEET FOR USE WITHOUT A PROTRACTOR



1. CIRCLE APPROPRIATE "ROOF SIDE" TO INDICATE OUTSIDE MITER OR INSIDE MITER. THIS DETAIL APPLIES FOR MITERS TIGHTER THEN 90° (ACUTE) OR WIDER THEN 90° (OBTUSE).
2. STARTING AT EITHER SIDE OF THE CORNER, MEASURE ALONG THE WALL EDGE A CONVENIENT DIMENSION, SUCH AS 24" OR 36", DEPENDING ON JOB SITE CONDITIONS. PLACE A MARK ON THE WALL AND RECORD MEASURED DIMENSION AS "DIM A" IN THE DRAWING ABOVE, REPEAT PROCEDURE FOR THE OPPOSITE WALL, AS SHOWN ABOVE.
3. MEASURE STRAIGHT ACROSS FROM MARK TO MARK, AS SHOWN, AND RECORD THE MEASURED DIMENSION AS "DIM B".
4. FAX THIS SHEET TO 800-373-9156 WITH ORDER.

PROJECT:
 ARCHITECT:
 ROOFING CONTRACTOR:
 REPRESENTATIVE/DISTRIBUTOR:

Customer Service
 Phone: 800-588-2162
 Fax: 800-373-9156
www.metalera.com/genflex



DATE: 02/18/21	SHT.# ___ OF ___
DRN BY: JJC	DWG# 22810-2368
CKD BY: MM	