



① STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE THICKER THAN .060".

② WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.

### FIBERTITE 200 FASCIA DIMENSIONS

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-95S	9 3/4"	7 3/8"	4 NAILERS
<input type="checkbox"/> FA-110S	11 1/4"	8 7/8"	5 NAILERS
<input type="checkbox"/> FA-125S	12 3/4"	10 3/8"	6 NAILERS

ANSI/SPRI/FM 4435/ ES-1  
DESIGN PRESSURE

FA-95 TO FA-125 IN .050 OR .063" - 116 psf

**AUTHORIZED SIGNATURE:**

**APPROVED BY:** \_\_\_\_\_

**DATE:** \_\_\_\_\_

### MATERIAL:

\_\_\_\_ 24 GA. GALV. STEEL      \_\_\_\_ .050" ALUMINUM  
\_\_\_\_ .040" ALUMINUM      \_\_\_\_ .063" ALUMINUM  
\_\_\_\_ OTHER \_\_\_\_\_

COLOR: \_\_\_\_\_ FINISH: \_\_\_\_\_

### QUANTITIES:

\_\_\_\_ LINEAL FEET 12'-0" LENGTHS  
\_\_\_\_ OUTSIDE MITER(S) @ 90°  
\_\_\_\_ INSIDE MITER(S) @ 90°  
\_\_\_\_ RIGHT ENDCAP(S)  
\_\_\_\_ LEFT ENDCAP(S)  
\_\_\_\_ RIGHT ENDWALL FLASHING(S)  
\_\_\_\_ LEFT ENDWALL FLASHING(S)  
\_\_\_\_ OVERFLOW SCUPPER(S) STYLE \_\_\_\_A\_\_\_\_B  
\_\_\_\_ SPILLOUT SCUPPER(S) STYLE \_\_\_\_A\_\_\_\_B  
\_\_\_\_ DOWNSPOUT SCUPPER(S) STYLE \_\_\_\_A\_\_\_\_B  
( \_\_\_\_X\_\_\_\_ ) SIZE      A: TAPERED 1 1/2" DROP  
   B: FLAT

SPECIFY ACCESSORY TYPE:  
☐ WELDED ②  
☐ STANDARD

FOR NON-90 MITERS SEE PRINT APPROVAL #23010-2417

PROJECT:

ARCHITECT:

ROOFING CONTRACTOR:

REPRESENTATIVE/DISTRIBUTOR:

CUSTOMER SERVICE  
800-355-6416

DATE: 11/02/16

DRN BY: JJC

CKD BY: SAK

SHT.# \_\_\_\_ OF \_\_\_\_

DWG# 23010-21533

E