REFERENCE DETAIL: **ECO-PERF TRUSS VEN** 24 GA. (.65 mm) STEEL MOUNTING BRACKET ADJUSTABLE BETWEEN **PERFORATED CHOSEN RANGE CLOSURE** WIDTH 5/₃₂"Ø (4 mm) HOLES (TYP. 2) ½" (13 mm) 24 GA. (.65 mm) PERFORATED CLOSURE 51% NET FREE AREA PROVIDED IN LONGEST LENGTH PER CHOSEN RANGE ½" (13 mm) Fabrication will proceed only after receipt of signed print approval. LENGTH RANGE: PERFORATED CLOSURE: MATERIAL: Print Approval: Architect and/or contractor shall verify all dimensions, sizes 14" (356 mm) to 20" (508 mm) 12 Sq In NFA (2" (51 mm) Width) 24 Ga. (.65 mm) Bone White and quantities. All products to be installed in strict accordance 20" (508 mm) to 28" (711 mm) 18 Sq In NFA (3" (76 mm) Width) 24 Ga. (.65 mm) Sandstone with Metal-Era's printed instructions. 28" (711 mm) to 40" (1.02 m) 24 Sq In NFA (4" (102 mm) Width) 24 Ga. (.65 mm) Dark Bronze Approved by: 40" (1.02 m) to 58" (1.47 m) Other 24 Ga. (.65 mm) Slate Gray Date: **QUANTITIES:** PROJECT: Phone: 800-558-2162 METAL ERA Fax: 800-770-3934 www.metalera.com Airflow Solutions ARCHITECT: DATE: 12/01/10 **Amount Required** SHT.#___ OF ___ CONTRACTOR: DRN BY: JJC DWG# 31032-12386 REPRESENTATIVE: CKD BY: SAK